



MOBILE

# RP2f Series Mobile Printer

The RPF Series mobile thermal printers are built for the most rugged environments, offering exceptional media and battery capacity, quiet operation, and excellent value to help operations increase efficiency and minimize downtime.

## Overview



This portable printer provides big productivity gains and reduces errors by enabling workers to print labels at the location they need, so labels can be applied when and where they need to be applied. The RPF printer comes with powerful CPU and smart power management – allowing smooth, continuous operation so your workers can work efficiently with less media reloading, battery swaps, and downtime. The RPF Series printer prints 25.4mm (1 in) to 104.1 mm (4.1 in) labels/receipts and can accommodate a wide variety of media, including the heavy stock necessary for hang tags and specialty label needs. Plus, its fast and easy-loading design means fewer interruptions and increased productivity in your application, whether using one type of media or several. The RPF Series has the latest 802.11 a/b/g/n/ac Wi-Fi capabilities for the best range and fast data communications on your WLAN. It also includes a Bluetooth 5.0 LE radio at no additional charge for when workers are outside of WLAN range or using the printer with a Bluetooth mobile computer. Built on Honeywell’s software platform, the RPF printer offers IT managers easy integrated device management, a high level of security throughout the entire printer lifespan, and upgrades that allow your printers to be updated with enhanced features.

## Specifications

### FEATURES

**Compatible Software**

- BarTender
- Nicelabel
- Operational Intelligence
- SOTI
- Teklynx Labelview

**Compatible Drivers**

- CUPS Driver for Linux
- Certified Device Types for SAP

- InterDriver Windows

## DIMENSIONS

---

### Overall Dimensions

- H x W x D: 160 mm x 116 mm x 77 mm (6.3 in x 4.6 in x 3.0 in)

## PRINTING SPECIFICATIONS

---

### Resolutions

- 203 dpi

### Print Speeds

- 25-125 mm/s (1-5 ips)

### Print Method

- Direct Thermal

## SOFTWARE & FIRMWARE

---

### Downloadable Font Type

- Bitmap Font
- OpenType Font (TrueType based)
- TrueType Font

### Linear Barcodes

- All major 1D barcodes

### 2D Barcodes

- All major 2D barcodes

### Printer Command Language

- C# Smart Printing
- CPCL
- DPL
- Direct Protocol (DP)
- EZ-Print
- Fingerprint (FP)
- Intermec Printer Language (IPL)
- PDF
- XML-enabled for SAP AII and Oracle WMS
- ZSim2 (ZPL-II)

### Image File Format

- BMP
- GIF
- PCX
- PNG

# MEDIA

**Printer Media Type**

- Label
- Lined
- Linerless
- Receipt
- Tag

**Maximum Media Roll Diameter**

- 58 mm (2.25 in)

# HARDWARE

**Printer Connection Interface**

- USB 2.0

# ELECTRICAL

**Battery Capacity Options**

- 2500 mAh

# ENVIRONMENTAL

**Operating Humidity**

- 20 - 80 % non-condensing

**Storage Humidity**

- 20 - 80 % non-condensing

# STANDARDS & APPROVALS

**Protection Ratings**

- IP54

**Drop Specifications**

- 2 m (6.6 ft)

**Tumble Specifications**

- 1,000 cycles at 0.5 m (1.6 ft)

# NETWORK

**Bluetooth Specifications**

- Bluetooth 5.0 + LE dual radio mode

# OTHERS

**Features**

- High power efficiency
- Rugged and reliable
- Smart printing

**Application**

- Healthcare
- Retail
- T&L

**Weight range**

- 0.72 kg (1.5 lb)with battery, no media keg

**Wireless Communication**

- IEEE 802.11 a/b/g/n/ac
- NFC for pairing
- OPEN, WEP, WPA/WPA2/WPA3 (Personal and Enterprise)

**Operating temperature**

- -20°C to 55°C (-4°F to 131°F)

**Storage Temperature**

- -30°C to 65°C (-22°F to 149°F)

**Warranty Duration**

- Two years factory warranty

**Platform**

- Honeywell Printer Edge

**Font Engine**

- Language support
- Monotype Font Engine
- WTLE for global

**Honeywell**  
Industrial Automation  
855 S Mint St  
Charlotte, NC 28202  
800-582-4263

**RP2f Series Mobile Printer**  
© 2024 Honeywell International Inc.  
All rights reserved.



This document was generated on 2024-06-06 15:16:44 (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.